

- 1. STREETLIGHT SPACING 200' UNLESS OTHERWISE NOTED. STREETLIGHTS AT ALL INTERSECTIONS SHALL BE 39W LED LIGHTS.
- 2. THE POLE MOUNTING HEIGHT SHALL BE 25FT RESIDENTIAL AND 27FT COMMERCIAL UNLESS OTHERWISE NOTED.
- 3. THE MAST ARM LENGTH SHALL 6 FT. SWEEP WITH A CUT OFF COBRA HEAD.
- 4. STREETLIGHTS AT MID-BLOCK LOCATIONS SHALL BE 31W LED LIGHTS.
- 5. ALL CUL-DE-SACS SHALL HAVE 31W LED LIGHTS LOCATED AT END.
- 6. ALL "ELBOWS" OR "KNUCKLES" IN ROADS SHALL HAVE 39W LED LIGHTS LOCATED AT EACH OF THEM.
- 7. STREETLIGHTS SHALL BE LOCATED AT LEAST FIVE (5) FEET FROM FIRE HYDRANTS AND 18 INCHES BEHIND THE CURBING.
- 8. ALL STREETLIGHTS SHALL BE LOCATED ON PROPERTY (LOT) LINES WHEREVER POSSIBLE.
- 9. THE TRAFFIC DIVISION OF PUBLIC WORKS WILL HANDLE SIGNALED INTERSECTION. COSTS OF THE LIGHTS AND ENERGY FOR THOSE INTERSECTIONS MUST GO THROUGH THAT DIVISION. (909)387-8192
- 10. STREELIGHT PLANS SHALL COMPLY WITH SCE DESIGN STANDARDS
- 11. EACH TRACT WILL BE REVIEWED INDIVIDUALLY. VARIANCES TO THE ABOVE WILL BE CONSIDERED AS THE SITUATION WARRANTS



## SAN BERNARDINO COUNTY DEPARTMENT OF PUBLIC WORKS

## STREETLIGHT DESIGN STANDARD DRAWING

NOEL CASTILLO, PE DIRECTOR OF PUBLIC WORKS/ROAD COMMISSIONER

> 314 SHEET 1 OF 1